Safety Data Sheet

Copyright,2019,3M Canada Company
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	19-2499-2	**Version number:**	7.03
Issue Date:	2019/02/04	**Supercedes Date:**	2016/05/20

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
3M FIRE BARRIER WATERTIGHT SEALANT 3000 WT

Product Identification Numbers
98-0400-5503-4 98-0400-5504-2 98-0400-5553-9 AK-2001-2921-6 XE-1014-9500-2
XE-1014-9924-4

1.2. Recommended use and restrictions on use

Intended Use
Caulk

Specific Use
Fire barrier caulking.

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Industrial Adhesives and Tapes Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place:
XE-1014-9924-4

2.1. Classification of the substance or mixture
Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1B.
Carcinogenicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark | Health Hazard |

Pictograms



Hazard statements

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause cancer.
Causes damage to organs: blood or blood-forming organs |

Causes damage to organs through prolonged or repeated exposure: blood or blood-forming organs |
May cause damage to organs through prolonged or repeated exposure: kidney/urinary tract |

Precautionary statements
General:
Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

Prevention:
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Call a POISON CENTRE or doctor/physician.

Storage:
Store locked up.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards
None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Melamine	108-78-1	30 - 60 Trade Secret *	1,3,5-Triazine-2,4,6-triamine
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	70131-67-8	15 - 40	Siloxanes and Silicones, di-Me, hydroxy-terminated
Graphite	7782-42-5	10 - 30	Graphite
Poly(Dimethylsiloxane)	63148-62-9	10 - 30	Siloxanes and Silicones, di-Me
Methyl Tris(2-Butylideneaminooxy)Silane	22984-54-9	3 - 7 Trade Secret *	2-Butanone, O,O',O''-(methylsilylidyne)trioxime
Silica	7631-86-9	0 - 5	Silica
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	0 - 5	Fumed amorphous silica, crystalline-free
(3-Aminopropyl)Triethoxysilane	919-30-2	0.5 - 1.5 Trade Secret *	1-Propanamine, 3-(triethoxysilyl)-
3-Iodo-2-Propynyl Butylcarbamate	55406-53-6	< 0.1	Carbamic acid, butyl-, 3-iodo-2-propynyl ester

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

5.3. Special protective actions for fire-fighters
Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid breathing of vapours created during cure cycle. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Melamine	108-78-1	AIHA	TWA(inhalable particulates):3 mg/m3	
Graphite	7782-42-5	ACGIH	TWA(respirable fraction):2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Appearance/Odour	Light gray with black flecks, thixotropic paste
Odour threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*Not Applicable*
Boiling point	*No Data Available*
Flash Point	No flash point
Evaporation rate	*No Data Available*
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapour Density	Nil
Relative density	1.25 [*Ref Std:*WATER=1]
Water solubility	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*Not Applicable*
Decomposition temperature	*No Data Available*
Viscosity	*No Data Available*
Molecular weight	*No Data Available*
Volatile Organic Compounds	<=5.3 % weight [*Test Method:*tested per EPA method 24]
Percent volatile	*No Data Available*
VOC Less H2O & Exempt Solvents	<=65 g/l [*Test Method:*tested per EPA method 24]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Not determined

10.5. Incompatible materials
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
Formaldehyde	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Oxides of Nitrogen	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

Prolonged or repeated exposure may cause target organ effects:
Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia. Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Melamine	108-78-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Melamine	Dermal	Rabbit	LD50 > 1,000 mg/kg
Melamine	Ingestion	Rat	LD50 3,161 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	Dermal	Rabbit	LD50 > 16,000 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	Ingestion	Rat	LD50 > 64,000 mg/kg
Graphite	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Graphite	Ingestion	Rat	LD50 > 2,000 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Methyl Tris(2-Butylideneaminooxy)Silane	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Methyl Tris(2-Butylideneaminooxy)Silane	Ingestion	Rat	LD50 2,260 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg
(3-Aminopropyl)Triethoxysilane	Dermal	Rabbit	LD50 4,290 mg/kg
(3-Aminopropyl)Triethoxysilane	Ingestion	Rat	LD50 1,570 mg/kg
3-Iodo-2-Propynyl Butylcarbamate	Dermal	Rabbit	LD50 > 2,000 mg/kg
3-Iodo-2-Propynyl Butylcarbamate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.67 mg/l
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Rat	LD50 1,056 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Melamine	Guinea pig	No significant irritation

Graphite	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
(3-Aminopropyl)Triethoxysilane	Rabbit	Corrosive
3-Iodo-2-Propynyl Butylcarbamate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Melamine	Rabbit	No significant irritation
Graphite	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
(3-Aminopropyl)Triethoxysilane	Rabbit	Corrosive
3-Iodo-2-Propynyl Butylcarbamate	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Melamine	Guinea pig	Not classified
Silica	Human and animal	Not classified
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human and animal	Not classified
(3-Aminopropyl)Triethoxysilane	Guinea pig	Sensitizing
3-Iodo-2-Propynyl Butylcarbamate	Multiple animal species	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Melamine	In Vitro	Not mutagenic
Melamine	In vivo	Not mutagenic
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	In Vitro	Not mutagenic
Graphite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica	In Vitro	Not mutagenic
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Melamine	Ingestion	Multiple animal species	Carcinogenic
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Synthetic Amorphous Silica, Fumed, Crystalline Free	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration

Melamine	Ingestion	Not classified for development	Rat	NOAEL 1,060 mg/kg/day	during organogenesis
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure
For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Melamine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 63 mg/kg/day	13 weeks
Graphite	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Silica	Inhalation	respiratory system | silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation	respiratory system | silicosis	Not classified	Human	NOAEL Not available	occupational exposure
3-Iodo-2-Propynyl Butylcarbamate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.00116 mg/l	90 days

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 2 **Flammability:** 0 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: *2 **Flammability:** 0 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	19-2499-2	**Version number:**	7.03
Issue Date:	2019/02/04	**Supercedes Date:**	2016/05/20

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca